

SELECTION TABLES FOR WR-150, WR-150-D

| NOMINAL DIMENSIONS (mm) | Ak (m ²) | DAMPER POSITION | Q | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 700 | 900 | 1000 | 1250 | 1500 | 2000 | 2500 | | |
|-------------------------|------------------------|-----------------|-----------|------|------|------|------|------|-------|-------|-------|------|------|------|------|------|------|---|---|
| (200x150) | 0,016 | 100% OPEN | V | 1,7 | 2,6 | 3,5 | 4,3 | 5,2 | 7,0 | - | - | - | - | - | - | - | - | - | |
| | | | ΔP | 2,3 | 4,5 | 8,0 | 12,5 | 17,0 | 30,0 | - | - | - | - | - | - | - | - | - | - |
| | | | La | <25 | <25 | 25 | 30 | 40 | 50 | - | - | - | - | - | - | - | - | - | - |
| | | 50% OPEN | Δp | 8,0 | 17,0 | 28,0 | 43,0 | 60,0 | 110,0 | - | - | - | - | - | - | - | - | - | - |
| | | | La | <25 | 30 | 40 | 50 | 50 | >50 | - | - | - | - | - | - | - | - | - | - |
| | | | ΔP | 17,0 | 38,0 | 60,0 | 95,0 | >100 | - | - | - | - | - | - | - | - | - | - | - |
| 25% OPEN | La | 25 | 40 | 45 | 50 | >50 | - | - | - | - | - | - | - | - | - | - | - | | |
| | (250x150) (200x200) | 0,021 | 100% OPEN | V | 1,3 | 2,0 | 2,6 | 3,3 | 4,0 | 5,3 | 6,6 | - | - | - | - | - | - | - | |
| | | | | ΔP | 1,2 | 2,8 | 4,5 | 7,0 | 11,0 | 17,5 | 28,5 | - | - | - | - | - | - | - | - |
| La | | | | <25 | <25 | <25 | 25 | 30 | 40 | 50 | - | - | - | - | - | - | - | - | |
| 50% OPEN | | | ΔP | 4,0 | 10,0 | 17,0 | 25,0 | 38,0 | 65,0 | 100,0 | - | - | - | - | - | - | - | - | - |
| | | | La | <25 | <25 | 30 | 35 | 45 | 50 | >50 | - | - | - | - | - | - | - | - | - |
| | | | ΔP | 4,0 | 22,0 | 38,0 | 55,0 | 80,0 | >100 | - | - | - | - | - | - | - | - | - | - |
| 25% OPEN | La | <25 | 30 | 40 | 45 | 50 | >50 | - | - | - | - | - | - | - | - | - | - | | |
| | (300x150) | 0,025 | 100% OPEN | V | - | 1,7 | 2,2 | 2,8 | 3,4 | 4,5 | 5,6 | 7,8 | - | - | - | - | - | - | |
| | | | | ΔP | - | 2,3 | 3,5 | 6,0 | 7,5 | 13,0 | 19,5 | 38,0 | - | - | - | - | - | - | - |
| La | | | | - | <25 | <25 | 25 | 25 | 35 | 45 | >50 | - | - | - | - | - | - | - | |
| 50% OPEN | | | ΔP | - | 8,0 | 13,0 | 20,0 | 27,0 | 45,0 | 73,0 | >100 | - | - | - | - | - | - | - | |
| | | | La | - | <25 | <25 | 30 | 35 | 50 | >50 | >50 | - | - | - | - | - | - | - | |
| | | | ΔP | - | 17,0 | 25,0 | 44,0 | 58,0 | 100,0 | - | - | - | - | - | - | - | - | - | |
| 25% OPEN | La | - | 25 | 30 | 40 | 45 | >50 | - | - | - | - | - | - | - | - | - | | | |
| | (350x150) (250x200) | 0,029 | 100% OPEN | V | - | 1,4 | 1,9 | 2,4 | 2,8 | 3,8 | 4,8 | 6,7 | - | - | - | - | - | - | |
| | | | | ΔP | - | 1,5 | 2,6 | 4,0 | 6,0 | 9,5 | 14,5 | 29,0 | - | - | - | - | - | - | |
| La | | | | - | <25 | <25 | <25 | 25 | 30 | 35 | 50,0 | - | - | - | - | - | - | | |
| 50% OPEN | | | ΔP | - | 5,0 | 10,0 | 14,0 | 20,0 | 35,0 | 50,0 | 105,0 | - | - | - | - | - | - | | |
| | | | La | - | <25 | <25 | 25 | 30 | 40 | 50 | >50 | - | - | - | - | - | - | | |
| | | | ΔP | - | 11,0 | 19,0 | 32,0 | 44,0 | 78,0 | >100 | - | - | - | - | - | - | | | |
| 25% OPEN | La | - | 25 | 30 | 35 | 40 | 50 | >50 | - | - | - | - | - | - | - | | | | |
| | (300x200) (250x250) | 0,034 | 100% OPEN | V | - | - | - | 2,0 | 2,5 | 3,3 | 4,1 | 5,7 | 7,4 | - | - | - | - | | |
| | | | | ΔP | - | - | - | 2,8 | 4,2 | 7,0 | 11,5 | 20,0 | 34,0 | - | - | - | - | | |
| La | | | | - | - | - | <25 | <25 | 25 | 30 | 45,0 | >50 | - | - | - | - | | | |
| 50% OPEN | | | ΔP | - | - | - | 10,0 | 15,0 | 25,0 | 40,0 | 76,0 | >100 | - | - | - | - | | | |
| | | | La | - | - | - | <25 | 30 | 35 | 45 | >50 | - | - | - | - | - | | | |
| | | | ΔP | - | - | - | 22,0 | 33,0 | 55,0 | 85,0 | >100 | - | - | - | - | | | | |
| 25% OPEN | La | - | - | - | 30 | 35 | 45 | 50 | >50 | - | - | - | - | - | | | | | |

Q: AIR FLOW RATE (m³/h)
 ΔP: PRESSURE DROP (Pa)
 V: DISCHARGE VELOCITY (m/s)
 La: NOISE LEVEL (dB(A))

SELECTION TABLES FOR WR-150, WR-150-D

| NOMINAL DIMENSIONS (mm) | Ak (m ²) | DAMPER POSITION | Q | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 700 | 900 | 1000 | 1250 | 1500 | 2000 | 2500 | | |
|-------------------------|----------------------|------------------------|-------|-----------|-----|-----|------|------|------|------|------|------|-------|------|------|------|------|---|---|
| (350x200) | 0,040 | 100% OPEN | V | - | - | - | 1,7 | 2,1 | 2,8 | 3,5 | 4,8 | 6,2 | 7,0 | - | - | - | - | | |
| | | | ΔP | - | - | - | 2,3 | 3,5 | 6,0 | 8,0 | 14,5 | 24,0 | 30,0 | - | - | - | - | - | |
| | | | La | - | - | - | <25 | <25 | 25 | 25 | 35 | 45 | 50 | - | - | - | - | - | |
| | | 50% OPEN | ΔP | - | - | - | 8 | 12 | 20 | 28 | 50,0 | 85,0 | 110,0 | - | - | - | - | - | |
| | | | La | - | - | - | <25 | 25 | 30 | 40 | 50,0 | >50 | >50 | - | - | - | - | - | |
| | | | ΔP | - | - | - | 17,0 | 23,0 | 44,0 | 60,0 | >100 | - | - | - | - | - | - | - | |
| | | 25% OPEN | La | - | - | - | 25 | 30 | 40 | 45 | >50 | - | - | - | - | - | - | - | |
| | | | V | - | - | - | 1,5 | 1,8 | 2,4 | 3,0 | 4,2 | 54,0 | 6,0 | - | - | - | - | - | |
| | | | ΔP | - | - | - | 1,6 | 2,4 | 4,0 | 6,0 | 12,0 | 18,0 | 22,0 | - | - | - | - | - | |
| (400x200) | 0,046 | 100% OPEN | La | - | - | - | <25 | <25 | <25 | 25 | 30 | 40 | 45 | - | - | - | - | | |
| | | | ΔP | - | - | - | 6,0 | 9,0 | 14,0 | 22,0 | 42,0 | 70,0 | 80,0 | - | - | - | - | | |
| | | | La | - | - | - | <25 | <25 | 25 | 30 | 50,0 | 50,0 | >50 | - | - | - | - | | |
| | | 50% OPEN | ΔP | - | - | - | 13,0 | 17,0 | 32,0 | 48,0 | 90,0 | >100 | - | - | - | - | - | - | |
| | | | La | - | - | - | <25 | 25 | 35 | 40 | 50 | >50 | - | - | - | - | - | - | |
| | | | V | - | - | - | - | - | 1,6 | 2,1 | 2,7 | 3,7 | 4,8 | 5,3 | 6,7 | - | - | - | |
| | | (450x200) (300x300) | 0,052 | 100% OPEN | ΔP | - | - | - | - | 2,0 | 3,5 | 5,5 | 9,5 | 14,5 | 17,5 | 29,0 | - | - | - |
| | | | | | La | - | - | - | - | <25 | <25 | <25 | 30 | 35 | 40 | 50 | - | - | - |
| | | | | | ΔP | - | - | - | - | 7,0 | 12,0 | 18,0 | 32,0 | 50,0 | 65,0 | 105 | - | - | - |
| 50% OPEN | La | | | - | - | - | - | <25 | 25 | 30 | 40,0 | 50,0 | 50,0 | >50 | - | - | - | | |
| | ΔP | | | - | - | - | - | 15,0 | 23,0 | 40,0 | 75,0 | >100 | - | - | - | - | - | | |
| | La | | | - | - | - | - | 25 | 30 | 40 | 50 | >50 | - | - | - | - | - | | |
| (500x200) (400x250) | 0,057 | | | 100% OPEN | V | - | - | - | - | - | 2,0 | 2,4 | 3,4 | 4,4 | 4,9 | 6,1 | 7,3 | - | - |
| | | | | | ΔP | - | - | - | - | - | 2,8 | 4,0 | 7,5 | 13,0 | 15,0 | 23,0 | 33,0 | - | - |
| | | | | | La | - | - | - | - | - | <25 | <25 | 25 | 30 | 35 | 45 | >50 | - | - |
| | | 50% OPEN | ΔP | - | - | - | - | - | 10,0 | 14,0 | 27,0 | 44,0 | 55,0 | 83,0 | >100 | - | - | | |
| | | | La | - | - | - | - | - | <25 | 25 | 35 | 50 | 50 | >50 | - | - | - | | |
| | | | ΔP | - | - | - | - | - | 22,0 | 32,0 | 57,0 | 97,0 | 105,0 | - | - | - | - | | |
| | | 25% OPEN | La | - | - | - | - | - | 30 | 35 | 35 | >50 | - | - | - | - | - | | |

Q: AIR FLOW RATE (m³/h)
 ΔP: PRESSURE DROP (Pa)
 V: DISCHARGE VELOCITY (m/s)
 La: NOISE LEVEL (dB(A))

SELECTION TABLES FOR WR-150, WR-150-D

| NOMINAL DIMENSIONS (mm) | Ak (m ²) | DAMPER POSITION | Q | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 700 | 900 | 1000 | 1250 | 1500 | 2000 | 2500 |
|-------------------------|----------------------|-----------------|----|-----|-----|------|------|------|------|------|-------|-------|------|-------|------|------|------|
| (300x250) | 0,043 | 100% OPEN | V | - | - | - | - | 2,0 | 2,5 | 3,2 | 4,5 | 5,8 | 6,5 | - | - | - | - |
| | | | ΔP | - | - | - | - | 2,8 | 4,2 | 7,0 | 13,0 | 21,0 | 28,0 | - | - | - | - |
| | | | La | - | - | - | - | <25 | <25 | 25 | 30 | 45 | 50 | - | - | - | - |
| | | 50% OPEN | ΔP | - | - | - | - | 10,0 | 15,0 | 23,0 | 45 | 78 | 95 | - | - | - | - |
| | | | La | - | - | - | - | <25 | 30 | 35 | 50 | >50 | - | - | - | - | - |
| | | 25% OPEN | ΔP | - | - | - | - | 22,0 | 33,0 | 50,0 | 100,0 | >100 | - | - | - | - | - |
| La | - | - | - | - | - | 30 | 35,0 | 45,0 | >50 | - | - | - | - | - | - | | |
| (500x250) | 0,073 | 100% OPEN | V | - | - | - | - | 1,5 | 1,9 | 2,7 | 3,4 | 3,8 | 4,8 | 5,7 | 7,6 | - | - |
| | | | ΔP | - | - | - | - | 1,6 | 25,0 | 5,5 | 7,5 | 9,5 | 14,5 | 20,0 | 36,0 | - | - |
| | | | La | - | - | - | - | <25 | <25 | <25 | 25 | 30 | 35 | 45 | >50 | - | - |
| | | 50% OPEN | ΔP | - | - | - | - | 6,0 | 10,0 | 18,0 | 27,0 | 35,0 | 50,0 | 76,0 | >100 | - | - |
| | | | La | - | - | - | - | <25 | <25 | 30,0 | 35 | 40 | 50 | >50 | - | - | - |
| | | 25% OPEN | ΔP | - | - | - | - | 12,0 | 19,0 | 40,0 | 58,0 | 78,0 | >100 | - | - | - | - |
| La | - | - | - | - | - | 25,0 | 30,0 | 40,0 | 45 | 50 | > | 50 | - | - | - | | |
| (350x300) | 0,061 | 100% OPEN | V | - | - | - | - | 1,8 | 2,3 | 3,2 | 4,1 | 4,6 | 5,7 | 6,8 | - | - | |
| | | | ΔP | - | - | - | - | 2,4 | 4,0 | 7,0 | 11,5 | 13,5 | 20,0 | 29,5 | - | - | |
| | | | La | - | - | - | - | <25 | <25 | 25,0 | 30 | 35 | 45 | 50 | - | - | |
| | | 50% OPEN | ΔP | - | - | - | - | 9,0 | 13,5 | 23,0 | 40,0 | 47,0 | 76,0 | 107,0 | - | - | |
| | | | La | - | - | - | - | <25 | <25 | 30,0 | 45 | 50 | >50 | - | - | - | |
| | | 25% OPEN | ΔP | - | - | - | - | 17,0 | 28,0 | 53,0 | 85,0 | 102,0 | >100 | - | - | - | |
| La | - | - | - | - | - | 25 | 35,0 | 50,0 | 50 | > | 50 | - | - | - | | | |
| (400x300) | 0,070 | 100% OPEN | V | - | - | - | - | 1,6 | 2,0 | 2,8 | 3,6 | 4,0 | 5,0 | 6,0 | - | - | |
| | | | ΔP | - | - | - | - | 2,0 | 2,8 | 6,0 | 9,0 | 11,0 | 16,0 | 22,0 | - | - | |
| | | | La | - | - | - | - | <25 | <25 | 25,0 | 30,0 | 30 | 40 | 45 | - | - | |
| | | 50% OPEN | ΔP | - | - | - | - | 7,0 | 10,0 | 20,0 | 30,0 | 38,0 | 58,0 | 80,0 | - | - | |
| | | | La | - | - | - | - | <25 | <25 | 30,0 | 35,0 | 45 | 50 | >50 | - | - | |
| | | 25% OPEN | ΔP | - | - | - | - | 15,0 | 22,0 | 44,0 | 62,0 | 80,0 | >100 | - | - | - | |
| La | - | - | - | - | - | 25 | 30 | 40,0 | 45,0 | 50 | >50 | - | - | - | | | |
| (500x300) | 0,088 | 100% OPEN | V | - | - | - | - | 1,6 | 2,2 | 2,8 | 3,1 | 4,0 | 4,7 | 6,3 | 8,0 | | |
| | | | ΔP | - | - | - | - | 2,0 | 3,5 | 6,0 | 6,5 | 11,0 | 14,0 | 25,0 | 40,0 | | |
| | | | La | - | - | - | - | <25 | <25 | 25 | 25 | 30 | 35 | 50 | >50 | | |
| | | 50% OPEN | ΔP | - | - | - | - | 7,0 | 13,0 | 20,0 | 23,0 | 38 | 48 | 90 | >100 | | |
| | | | La | - | - | - | - | <25 | <25 | 30,0 | 30,0 | 45 | 50 | >50 | - | | |
| | | 25% OPEN | ΔP | - | - | - | - | 15,0 | 25,0 | 44,0 | 50,0 | 80,0 | >100 | - | - | | |
| La | - | - | - | - | - | 25 | 30 | 40 | 40 | 50 | >50 | - | - | | | | |

Q: AIR FLOW RATE (m³/h)
 ΔP: PRESSURE DROP (Pa)
 V: DISCHARGE VELOCITY (m/s)
 La: NOISE LEVEL (dB(A))



SELECTION TABLES FOR WR-150, WR-150-D

| NOMINAL DIMENSIONS (mm) | Ak (m ²) | DAMPER POSITION | Q | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 700 | 900 | 1000 | 1250 | 1500 | 2000 | 2500 | | | |
|-------------------------|----------------------|-----------------|-------|-----------|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|-------|------|------|------|
| (600x300) (500x400) | 0,107 | 100% OPEN | V | - | - | - | - | - | - | - | 1,8 | 2,3 | 2,6 | 3,2 | 3,9 | 5,2 | 6,5 | | | |
| | | | ΔP | - | - | - | - | - | - | - | - | 2,4 | 4,0 | 4,5 | 7,0 | 10,0 | 17,0 | 28,0 | | |
| | | | La | - | - | - | - | - | - | - | - | <25 | <25 | <25 | 25 | 30 | 40 | 50,0 | | |
| | | 50% OPEN | ΔP | - | - | - | - | - | - | - | - | 9,0 | 13,5 | 17,0 | 24 | 37 | 60 | 98,0 | | |
| | | | La | - | - | - | - | - | - | - | - | <25 | <25 | 30,0 | 30 | 45 | 50 | >50 | | |
| | | | ΔP | - | - | - | - | - | - | - | - | 17,0 | 30,0 | 38,0 | 52,0 | 79,0 | >100 | - | | |
| | | 25% OPEN | La | - | - | - | - | - | - | - | - | 25 | 35 | 40 | 45 | 50 | >50 | - | | |
| | | | V | - | - | - | - | - | - | - | - | 1,6 | 2,0 | 2,2 | 2,8 | 3,3 | 4,5 | 5,6 | | |
| | | | ΔP | - | - | - | - | - | - | - | - | 2,0 | 2,8 | 3,5 | 6,0 | 7,0 | 13,0 | 19,5 | | |
| (700x300) | 0,125 | 100% OPEN | La | - | - | - | - | - | - | - | <25 | <25 | <25 | 25 | 25 | 35 | 45,0 | | | |
| | | | ΔP | - | - | - | - | - | - | - | - | 7,0 | 10,0 | 13,0 | 20 | 25 | 45 | 73,0 | | |
| | | | La | - | - | - | - | - | - | - | - | <25 | <25 | <25 | 30 | 35 | 50 | >50 | | |
| | | 50% OPEN | ΔP | - | - | - | - | - | - | - | - | 15,0 | 22,0 | 25,0 | 44,0 | 55,0 | 100,0 | >100 | | |
| | | | La | - | - | - | - | - | - | - | - | 25 | 30 | 30 | 40 | 45 | >50 | - | | |
| | | | V | - | - | - | - | - | - | - | - | - | - | 2,0 | 2,3 | 3,1 | 3,8 | - | | |
| | | (1000x300) | 0,180 | 100% OPEN | ΔP | - | - | - | - | - | - | - | - | - | 2,8 | 4,0 | 6,5 | 9,5 | - | |
| | | | | | La | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 25 | 30 | - |
| | | | | | ΔP | - | - | - | - | - | - | - | - | - | - | 10,0 | 13,5 | 23,0 | 35,0 | - |
| 50% OPEN | La | | | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 30 | 40 | - | | |
| | ΔP | | | - | - | - | - | - | - | - | - | - | - | 22,0 | 30,0 | 50,0 | 78,0 | - | | |
| | La | | | - | - | - | - | - | - | - | - | - | - | 30 | 35 | 40 | 50 | - | | |
| (400x400) | 0,095 | | | 100% OPEN | V | - | - | - | - | - | - | 2,0 | 2,6 | 3,0 | 3,6 | 4,4 | 5,8 | 7,3 | - | |
| | | | | | ΔP | - | - | - | - | - | - | - | - | 2,8 | 4,5 | 6,0 | 9,5 | 13,0 | 21,0 | 33,0 |
| | | | | | La | - | - | - | - | - | - | - | - | <25 | <25 | 25 | 30 | 45 | >50 | - |
| | | 50% OPEN | ΔP | - | - | - | - | - | - | - | - | 10 | 17 | 22 | 30 | 44 | 78 | >100 | - | |
| | | | La | - | - | - | - | - | - | - | - | <25 | 30 | 30 | 35 | 50 | >50 | - | - | |
| | | | ΔP | - | - | - | - | - | - | - | - | 22,0 | 38,0 | 48,0 | 62,0 | 97,0 | >100 | - | - | |
| | | 25% OPEN | La | - | - | - | - | - | - | - | - | 30 | 40 | 40 | 45 | >50 | - | - | - | |
| | | | V | - | - | - | - | - | - | - | - | - | - | 2,0 | 2,4 | 2,9 | 3,9 | 4,8 | - | |
| | | | ΔP | - | - | - | - | - | - | - | - | - | - | 2,8 | 4,0 | 6,0 | 10,0 | 14,5 | - | |
| (600x400) | 0,144 | 100% OPEN | La | - | - | - | - | - | - | - | - | - | <25 | <25 | 25 | 30 | 35 | - | | |
| | | | ΔP | - | - | - | - | - | - | - | - | - | 10,0 | 14,0 | 21,0 | 36,0 | 50,0 | - | | |
| | | | La | - | - | - | - | - | - | - | - | - | <25 | 25 | 30 | 40 | 50 | - | | |
| | | 50% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | 22,0 | 32,0 | 46,0 | 79,0 | >100 | - | |
| | | | La | - | - | - | - | - | - | - | - | - | - | 30 | 35 | 40 | 50 | - | - | |
| | | | V | - | - | - | - | - | - | - | - | - | - | 2,0 | 2,4 | 2,9 | 3,9 | 4,8 | - | |
| | | 25% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | 2,8 | 4,0 | 6,0 | 10,0 | 14,5 | - | |
| | | | La | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 25 | 30 | 35 | - | |
| | | | ΔP | - | - | - | - | - | - | - | - | - | - | 10,0 | 14,0 | 21,0 | 36,0 | 50,0 | - | |
| 25% OPEN | La | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 25 | 30 | 35 | - | | | |

Q: AIR FLOW RATE (m³/h)
 ΔP: PRESSURE DROP (Pa)
 V: DISCHARGE VELOCITY (m/s)
 La: NOISE LEVEL (dB(A))



SELECTION TABLES FOR WR-150, WR-150-D

| NOMINAL DIMENSIONS (mm) | Ak (m ²) | DAMPER POSITION | Q | 150 | 200 | 250 | 300 | 400 | 500 | 700 | 900 | 1000 | 1250 | 1500 | 2000 | 2500 | 5000 | | |
|-------------------------|----------------------|-----------------|----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|-------|---|
| (1000x400) | 0,243 | | V | - | - | - | - | - | - | - | - | - | - | 1,7 | 2,3 | 2,8 | 5,7 | | |
| | | 100% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | 2,3 | 4,0 | 6,0 | 20,0 | |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 25 | 45 | |
| | | 50% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | 8,0 | 13,5 | 20,0 | 76,0 | |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 30 | >50 | |
| | | 25% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | 17,0 | 28,0 | 44,0 | >100 | |
| La | - | - | - | - | - | - | - | - | - | - | - | - | 25 | 35 | 40 | >50 | | | |
| (500x500) | 0,151 | | V | - | - | - | - | - | - | - | - | - | 2,3 | 2,8 | 3,7 | 4,6 | - | | |
| | | 100% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | 4,0 | 6,0 | 9,5 | 13,5 | - | |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 30 | 35 | - |
| | | 50% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | 13,5 | 20,0 | 32,0 | 47,0 | - |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | <25 | 30 | 40 | 50 | - |
| | | 25% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | 28,0 | 44,0 | 75,0 | 102,0 | - |
| La | - | - | - | - | - | - | - | - | - | - | - | - | 35 | 40 | 50 | >50 | - | | |
| (1000x500) | 0,306 | | V | - | - | - | - | - | - | - | - | - | - | - | 1,8 | 2,3 | 4,5 | | |
| | | 100% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | - | 2,4 | 4,0 | 13,0 | |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 35 | |
| | | 50% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | - | 9,0 | 13,5 | 45,0 | |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 50 | |
| | | 25% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | - | 17,0 | 28,0 | >100 | |
| La | - | - | - | - | - | - | - | - | - | - | - | - | - | 25 | 35 | >50 | | | |
| (600x600) | 0,219 | | V | - | - | - | - | - | - | - | - | - | - | 1,9 | 2,5 | 3,2 | 6,4 | | |
| | | 100% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | 2,6 | 4,2 | 7,0 | 26,0 | |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 25 | 50 | |
| | | 50% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | 10 | 15 | 23 | 93,0 | |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | <25 | 30 | 35 | >50 | |
| | | 25% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | 19,0 | 33,0 | 50,0 | >100 | |
| La | - | - | - | - | - | - | - | - | - | - | - | - | 30 | 35 | 45 | >50 | | | |
| (1000x600) | 0,369 | | V | - | - | - | - | - | - | - | - | - | - | - | 1,5 | 1,9 | 3,8 | | |
| | | 100% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | - | 1,6 | 2,6 | 9,5 | |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 30 | |
| | | 50% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | - | 6 | 10 | 35,0 | |
| | | | La | - | - | - | - | - | - | - | - | - | - | - | - | <25 | <25 | 40 | |
| | | 25% OPEN | ΔP | - | - | - | - | - | - | - | - | - | - | - | - | 13,0 | 19,0 | 78,0 | |
| La | - | - | - | - | - | - | - | - | - | - | - | - | - | <25 | 30 | 50 | | | |

Q: AIR FLOW RATE (m³/h)
 ΔP: PRESSURE DROP (Pa)
 V: DISCHARGE VELOCITY (m/s)
 La: NOISE LEVEL (dB(A))

