

ΠΙΝΑΚΑΣ ΕΠΙΛΟΓΗΣ ΣΤΟΜΙΩΝ FA-450-C

ΟΝΟΜΑΣΤΙΚΟ ΜΕΓΕΘΟΣ (mm)	Ak (m ²)	Q	200	250	300	400	500	600	700	800	900	1000	1250	1500	2000	
Φ200	0,0314	V	1,7	2,0	2,5	3,3	4,0	5,0	-	-	-	-	-	-	-	
		ΔP	12,0	16,0	30,0	60,0	100,0	150,0	-	-	-	-	-	-	-	
		La	<25	30	40	45	55	>60	-	-	-	-	-	-	-	
Φ250	0,0491	V	-	1,4	1,6	2,3	2,8	3,3	3,7	4,5	4,8	-	-	-	-	
		Δp	-	7,0	11,0	24,0	40,0	60,0	80,0	125,0	150,0	-	-	-	-	
		La	-	<25	25	35	40	45	55	60	>60	-	-	-	-	
Φ300	0,0779	V	-	-	-	1,5	1,8	2,2	2,5	3,0	3,2	3,6	4,2	4,5	-	
		Δp	-	-	-	8,0	14,0	22,0	30,0	45,0	60,0	80,0	110,0	125,0	-	
		La	-	-	-	<25	30	35	40	45	45	50	55	60	-	
Φ350	0,1010	V	-	-	-	-	1,5	1,7	2,0	2,3	2,5	3,0	3,5	4,2	-	
		Δp	-	-	-	-	8,0	12,0	16,0	24,0	30,0	45,0	70,0	110,0	-	
		La	-	-	-	-	<25	<25	30	35	40	45	50	55	-	
Φ400	0,125	V	-	-	-	-	-	-	1,6	1,8	2,0	2,3	3,0	3,5	4,5	
		ΔP	-	-	-	-	-	-	-	9,0	14,0	16,0	24,0	45,0	70,0	125,0
		La	-	-	-	-	-	-	-	<25	30	30	35	45	50	60

Q: ΠΑΡΟΧΗ ΑΕΡΑ (m³/h)
 V: ΤΑΧΥΤΗΤΑ ΕΞΟΔΟΥ (m/s)
 Δp: ΠΤΩΣΗ ΠΙΕΣΗΣ (Pa)
 La: ΣΤΑΘΜΗ ΘΟΡΥΒΟΥ (dB(A))